

## FHB71600v0+LA11201



Product Code:

FHB71600v0+LA11201

## Electrical Data

Voltage (V)	220-240V
Frequency (Hz)	50/60
Input Current (mA)	457
Power Factor ( $\lambda$ )	0.9

## Product Data

Product Wattage (W)	101
Light Source	Integrated LED-4000
Colour Temperature (K)	4000
Colour Render Index (Ra)	Ra80
Protection Class	CL I
Colour Consistency (SDCM)	6
Dimmable	No
Operating Temperature	-30°C to +50°C
Ambient Temperature Range (Ta)	50
Switching Cycles (times)	100,000
Weight (g)	1980
Application	Retails, Exhibitions, Halls, High-ceilings, Manufacturing Bays, Trade Fairs, Warehouses

## Performance Data

Rated Useful Luminous Flux (lm)	13500
Rated Life (hrs)	50,000hrs L70B50@Ta40°C
IP Rating	IP65/IP65

## Product Dimensions

Diameter (mm)	262
Height (mm)	190

Product Code: FHB71600v0+LA11201

MEGAMAN® 2005-2024. All Rights Reserved.

This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

[www.hk.megaman.cc](http://www.hk.megaman.cc)